

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Gaskets and Sealings**with type designation(s)
Flat Gasket - KLINGER®top-graph 2000

Issued to

Rich. Klinger Dichtungstechnik GmbH & Co. KG
Gumpoldskirchen, Niederösterreich, Austria

is found to comply with

ASTM F36
DIN 28090**Application :****Refer to section Application in the certificate.****Temperature range:** Refer to certificate and manufacturer's instruction.**Max. working** Refer to certificate and manufacturer's instruction.**press.:****Design:** Plate material**Sizes:** 1000 x 1500 mm, 2000 x 1500 mm; Thicknesses [mm]: 0.5, 1.0, 1.5,
2.0, 3.0Issued at **Hamburg** on **2019-08-30**This Certificate is valid until **2024-08-26**.DNV GL local station: **Augsburg**for **DNV GL**Approval Engineer: **Hagen Markus**.....
Olaf Drews
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-029482-1**
Certificate No: **TAP00001HT**
Revision No: **1**

PRODUCT DESCRIPTION

KLINGER®top-graph 2000

Asbestos free flat gasket material based on graphite and synthetic fibres.

Dimensions of plate material:

- Sizes: 1000 x 1500 mm, 2000 x 1500 mm
- Thicknesses: 0.5 mm, 1.0 mm, 1.5 mm, 2.0 mm, 3.0 mm
- Tolerances: Thickness acc. DIN 28091-1
Length ± 50 mm, width ± 50 mm

Typical values for 2.0 mm thickness:

| Technical data | Standard | Conditions | Value | Unit |
|--------------------------|-------------|----------------|-------|-------------------|
| Density | DIN 28090-2 | -- | 1.8 | g/cm ³ |
| Compressibility | ASTM F36J | -- | 10 | % |
| Recovery | ASTM F36J | -- | 60 | % |
| Tightness | DIN 28090-2 | -- | 0.05 | mg/s*m |
| Klinger cold compression | Klinger | 50 MPa / 23°C | 10 | % |
| Klinger hot compression | Klinger | 50 MPa / 300°C | 10 | % |

Note¹ : Reference "Declaration of conformity acc. to DIN EN ISO 17050-1" issued by KLINGER Dichtungstechnik GmbH & Co. KG, 2019-05-27.

APPLICATION

The above listed gasket material sheet type may be used under consideration of the mechanical and technical characteristics as well as physical and chemical properties for the following applications:

- On board ships and other structures classed by DNV GL as follows:
Ship's piping systems as specified in DNV GL Rules Pt.4, Ch.6 Piping systems and cargo lines on oil tankers.
Excluding cargo lines on chemical and gas tankers, carrying flammable and/or noxious media, propylene oxide and mixtures of ethylene and propylene oxide.
Excluding pipe lines for LNG, flammable gas systems and cryogenic fluids.
- The selection of the gaskets for the corresponding application and appropriate installation has to be in accordance with the instructions of the manufacturer.

TYPE APPROVAL DOCUMENTATION

TESTS CARRIED OUT

Documentation of tests performed and referenced in the list above are the basis for this type approval.

Job Id: **262.1-029482-1**
Certificate No: **TAP00001HT**
Revision No: **1**

MARKING OF PRODUCT

For traceability of products, marking shall be legible and indelible. Products are to be marked at least as follows:

- Manufacturer's name / label
- Product type / name

Marking sample: **KLINGER®top-graph-2000**

PERIODICAL ASSESSMENT

A condition for retention of the type approval certificate in its validity period is that periodical assessments are successfully carried out. The objective of the periodical assessment is to verify that the conditions for the type approval have not been altered. Regulations for the periodical assessment of the type approval certificate are to be found in the DNVGL Class Programme CP-0338.

It is further to be noted that the Society shall be informed of any:

- Modifications to the product which are liable to affect its characteristics and functions, as originally specified and tested;
- Shifting of the production site and additional production site.

If such notifications are not made, the validity of the type approval certificate terminates.

END OF CERTIFICATE